

# d-Color

P2226/P2226plus

## Combining mobile printing efficiency with vibrant colour

High productivity, excellent image quality and **rapid printing** are the key elements of the Olivetti d-Color P2226/P2226plus laser printers.

These models are provided with a high-performance print controller which processes data swiftly and delivering output in brilliant colours. With their versatile connections and system compatibility with the “mobile” world productivity is improved even further. The combination of simple operation, professional output and application versatility all help to accelerate office workflow.

The d-Color P2226/P2226plus have been designed to have a low impact on the environment and on your budget thanks to the use of **long life components**.

For added productivity, the printers also provide duplex printing, Gigabit Ethernet and a convenient 2-row LCD display.

What is more, the d-Color P2226plus model is delivered with **standard Wi-Fi and Wi-Fi Direct connectivity**.

UP TO 26 PAGES PER MINUTE IN A4 FORMAT, IN BOTH MONO AND COLOUR

PRINTING QUALITY UP TO 1200 DPI

DUPLEX UNIT PROVIDED AS STANDARD

TIME FOR FIRST PRINTOUT: 9.5 SECS IN MONO, 10.5 SECS IN COLOUR

HIGH-PERFORMANCE CONTROLLER - 800 MHZ CPU

WI-FI AND WI-FI DIRECT AS STANDARD (FOR D-COLOR P2226PLUS)

"MOBILE" PRINT COMPATIBILITY - AIR PRINT, OLIVETTI

MOBILE PRINTING

COMPACT DESIGN WITH LOW NOISE LEVELS

### Colour laser printers

COLOUR



SPEED



COMPACT



NETWORK



SILENT



ECO-FRIENDLY



QUALITY



WI-FI AND WI-FI-DIRECT \*



\* d-Color P2226plus only





USB host Interface



Easy-to-replace toner



Versatile paper handling

## TECHNICAL SPECIFICATIONS

### GENERAL

|  |   |
|--|---|
| <b>Type</b>  | Desk-top Printer  |
| <b>Technology</b>                                    | Colour Laser  |
| <b>Speed</b>   | 26 ppm A4 Mono and Colour   |
| <b>Processor</b>                                     | 800 MHz   |
| <b>Resolution</b>                                    | 1,200 x 1,200 dpi printing, multibit technology up to 9,600 x 600 dpi (printing), 600 x 600 dpi   |
| <b>Emulations</b>                                    | PCL 6 (PCL-XL /PCL-5c)-XL, KPDL 3 (PostScript 3 compatible), PDF Direct Print, XPS Direct Print   |
| <b>Operating Systems</b>                             | All current Windows operating systems, Mac OS X Version 10.8 or later, UNIX, LINUX  |
| <b>Font/Barcodes</b>                                 | 93 scalable fonts (PCL)/Postscript, 8 fonts (Windows Vista), 1 Bitmap font, 45 barcode types (EAN 8, EAN 13, EAN128) plus two-dimensional barcodes (PDF-417) (PCL and other barcodes available as options)  |
| <b>Mobile Printing Support</b>                       | Olivetti Mobile Print to iOS and Android, AirPrint, Google Cloud Print, Wi-Fi Direct (d-Color P2226plus only)   |
| <b>Display</b>                                       | 2-row LCD   |
| <b>Warm-up Time</b>                                  | Approx 29 secs or less  |
| <b>Time to First Print-out</b>                       | Mono approx. 9.5 secs; Colour approx. 10.5 secs   |
| <b>Memory</b>  | Standard 512 MB, max 512 MB   |
| <b>Paper Input Tray</b>                              | - Universal By-pass 50 sheets, 60 - 220 g/m <sup>2</sup> , A4, A5, A6, B5, B6 Letter, Legal, Custom (70 x 148mm-216 x 356mm)<br>- Universal Tray 250 sheets, 60 -163 g/m <sup>2</sup> , A4, A5, A6, B5, B6 Letter, Legal, Custom (105 x 148mm - 216 x 356mm)<br>- Max Paper Input Capacity max: 550 sheets (with optional Tray PF-5110 - B3420) |
| <b>Duplex Printing</b>                               | Automatic; 60-120 g/m <sup>2</sup> , A4, A5, B5, Letter, Legal  |
| <b>Paper Output Capacity</b>                         | Max 150 sheets, face-down   |
| <b>Standard Interfaces</b>                           | USB 2.0 (Hi-Speed), USB Host Interface, Gigabit Ethernet (10 Base-T/100 Base-TX/1000 Base-T), optional SD/SDHC Card slot, Wireless LAN (d-Color P2226plus only)   |
| <b>Dimensions (W x D x H)</b>                        | Base unit: 410 x 410 x 329 mm   |
| <b>Weight</b>  | Base unit 21 kg approx  |
| <b>Power Supply</b>                                  | 220 V ~ 240 V, 50/60 Hz   |
| <b>Power Consumption, Printing</b>                   | 375 W   |
| <b>Power Consumption, Standby</b>                    | 33 W  |
| <b>Power Consumption, Sleep mode</b>                 | Approx 0.9 W  |
| <b>Noise Levels (according to ISO 7779/ISO 9296)</b> | - Printing: 47.4 dB (A) LpA<br>- Standby: 30 dB (A) LpA<br>- Sleep: less than measurable levels   |
| <b>Security Standards</b>                            | GS, TÜV, EC. This product is manufactured by a company operating in conformity with ISO 9001 quality standards and ISO 14001 environmental directives. RoHs compatibility   |

### CONSUMABLES

|  |  |
|--|--|
| <b>Toner Cartridge Black (B1237)</b>   | Up to 4,000 A4 pages according to ISO 19798; (initial supply up to 1,200 A4 pages) |
| <b>Toner Cartridge Cyan (B1238)</b>    | Up to 3,000 A4 pages according to ISO 19798; (Initial supply up to 1,200 A4 pages) |
| <b>Toner Cartridge Magenta (B1239)</b> | Up to 3,000 A4 pages according to ISO 19798; (Initial supply up to 1,200 A4 pages) |
| <b>Toner Cartridge Yellow (B1240)</b>  | Up to 3,000 A4 pages according to ISO 19798; (Initial supply up to 1,200 A4 pages) |

### OPTIONS

|  |  |
|--|--|
| <b>PF-5110 (B3420)</b>                     | Maximum of 1 optional additional Tray Universal Paper Tray, 250 sheets, 60 - 163 g/m <sup>2</sup> , A4, A5, A6, B5, B6 Letter, Legal, Custom (105 x 148mm - 216 x 356mm) |
| <b>UG-33 (B8403)</b>                       | Thin Print protocol support module   |
| <b>Card Authentication Kit (B) (B8237)</b> | Various authentication types supported   |
| <b>PCL barcode Flash 3.0 (B4998)</b>       | Contains 45 single-dimension and two-dimension fonts, PDFs and Maxicode 417  |

Performance relates to use of the product under optimal conditions. Right reserved to modify technical specifications.

Registered trademarks are the property of their respective owners. d-Color P2226/P2226plus are distributed by Olivetti S.p.A.

(02/2017) - Codice: 49561-00-w